



SSA-R

SPLIT SINGLE AXLE REEL TRAILER



Boss Products, Inc.
602 Maple Lane
Wakarusa, Indiana 46573
Office: 574-970-0450

sales@bossproductsinc.com
www.PoleCatTrailers.com

TRAILER SPECIFICATIONS

GVWR	8,000 lbs./3,629 kg
Frame Construction	Steel Tube
Trailer Weight	1,580 lbs./717 kg
Trailer Width	7 ft. 11 3/4 in.
Trailer Length	10 ft.
Tire Sizes	215/75R17.5
Wheels per Axle	2
GAWR	8,000 lbs. Split Axle
Suspension	None
Towing Electrical Plug	7-way RV Plug
Brake System	Electric with Breakaway Kit
Lighting	US DOT Regulation LED
Color	Plascoat® White Finish

ACCESSORIES

Wheel Chocks	2
Clevis Hooks on Safety Chains	3/8 in.
Lunette Ring (with 4 mounting height locations)	2 1/2 in. I.D.
Square Sidewind Hitch Jack	5,000 lbs./2,268 kg. 28 1 11/16 in. lift
Document Holder	1
Mud Flaps	
Anti-Spin Reel Transportation Chain	1

REEL SPECIFICATIONS

Max Reel Width	60 in.
Max Reel Diameter	108 in./120 in. with reel inches off ground
Max Reel Lifting Weight	6,420 lbs./2,912 kg.
Solid Cold Rolled Steel Shaft	2.87 in.
Locking Reel Collars	12 in. O.D. (2)
Manual Prince Hydraulic Pump	1 Gallon Reservoir and 3,000 PSI Capacity
Reel Lift Travel	19.375 in.

